




FZ42


5-AXIS PORTAL MILLING MACHINE




Illustrations are similar.
Subject to technical modifications.

AT THE HEART OF THE FZ42: OUR VH60 MILLING HEAD.

The FZ42 compact is equipped with the **dynamic 2-axis VH60 milling head** (A-axis and C-axis). This extremely efficient milling head features a flexible MuST® spindle change system for precise execution of complex milling jobs. Roughing and finishing of various workpieces can be carried out without reclamping, which considerably reduces setup times. Different milling processes can be performed in a single setup. The VH60 can be fitted with three MuST® milling spindles. The drives, which incorporate zero-play torque motors, ensure outstanding dynamic behavior and maximum material removal rates in the machining of different materials. The VH60 is designed for high-performance machining of hard and tough materials, such as titanium, steel, light metals and cast iron.



Torque / Output diagram VH60 – 84 hp (63 kW)



Torque / Output diagram VH60 – 125hp (93 kW)

TECHNICAL DATA.

FZ42

Working Ranges

X-axis	118"-1575" (3 000 – 40 000 mm)
Y-axis	98"-236" (2 500 – 6 000 mm)
Z-axis	39"-118" (1 000 – 3 000 mm)

Table Size

Length	118"-1575" (3 000 – 40 000 mm)
Width	98"-236" (2 500 – 6 000 mm)
Height	250 mm (10")
Table load	max. 15 000 kg/m ²
T-Slots (longitudinal)	18 ^{H12}
Pitch of T-slots	10" (250 mm)

Drives – Linear Axes

Feed rate	X-, Y-, Z-axis	up to 2 362 ipm (60 m/min)
Acceleration	X-, Y-, Z-axis	up to 157.4 in/s ² (4 m/s ²)

Dimensions

Required space (without peripherals)	Length	307"-1882" (7 800 – 47 800 mm)
	Width	262"-400" (6 650 – 10 150 mm)
	Height	221"-359" (5 610 – 9 110 mm)

Accuracy

Standard accuracy	in accordance to VDI / DGQ 3441 or ISO 230-2
Special accuracy	on request

MILLING HEAD VH60

Performance

Torque rotary axes	in control	A-, C-axis: 2213 ft lb (3 000 Nm)
	clamped	A-axis: 4130 ft lb (5 600 Nm)
		C-axis: 4425 ft lb (6 000 Nm)

Swivelling Range

A-axis	± 110°
C-axis	± 360°

Drives – Rotary Axes

Rate of feed A-, C-axis	A-, C-axis	360°/s
Acceleration A-, C-axis	A-, C-axis	700°/s ²
Resolution	A-, C-axis	0.0001°

Accuracy

Positioning accuracy	A-, C-axis	10"
Repeatability	A-, C-axis	6"

MILLING HEAD VH60

Milling Spindle – 84 hp (63 kW)*

Spindle power	S1 (100 %)	84 hp (63 kW)
	S6 (40 %/2 min)	110 hp (82 kW)
Spindle speed	15 000 rpm	
	Torque	
Torque	S1 (100 %)	221 ft lb (300 Nm)
	S6 (40 %/2 min)	289 ft lb (392 Nm)
Constant power	S1 (100 %)	
	2 000 – 15 000 rpm	
Swivel axis – spindle nose	15" (385 mm)	
	Tool holder	
HSK-A100		
Tool clamping		spring clamp
Tool unclamping		hydraulic
Lubrication		oil mist lubrication

Milling Spindle – 125 hp (93 kW)*

Spindle power	S1 (100 %)	125 hp (93 kW)
	S6 (40 %/2 min)	138 hp (103 kW)
Spindle speed	8 000 rpm	
	Torque	
Torque	S1 (100 %)	327 ft lb (444 Nm)
	S6 (40 %/2 min)	408 ft lb (553 Nm)
Constant power	S1 (100 %)	
	2 000 – 8 000 rpm	
Swivel axis – spindle nose	15" (385 mm)	
	Tool holder	
HSK-A100		
Tool clamping		spring clamp
Tool unclamping		hydraulic
Lubrication		oil mist lubrication

MuST® Spindle Changing System

Roughing Spindle 1 – 59 hp (44 kW)

Spindle power	S1 (100 %)	59 hp (44 kW)
	S6 (40 %/2 min)	56 hp (42 kW)
Spindle speed	10 000 rpm	
	Torque	
Torque	S1 (100 %)	148 ft lb (200 Nm)
	S6 (40 %/2 min)	170 ft lb (230 Nm)

Roughing Spindle 2 – 60 hp (45 kW)

Spindle power	S1 (100 %)	60 hp (45 kW)
	S6 (40 %/2 min)	80 hp (60 kW)
Spindle speed	5 000 rpm	
	Torque	
Torque	S1 (100 %)	254 ft lb (344 Nm)
	S6 (40 %/2 min)	335 ft lb (454 Nm)

Universal Spindle – 67 hp (50 kW)

Spindle power	S1 (100 %)	67 hp (50 kW)
	S6 (40 %/2 min)	78 hp (58 kW)
Spindle speed	24 000 rpm	
	Torque	
Torque	S1 (100 %)	70 ft lb (95 Nm)
	S6 (40 %/2 min)	92 ft lb (117 Nm)

* Other spindle dimensions on request.

We reserve the right to make technical changes without prior notice.

Zimmermann Inc.

A 30587 Century Drive
Wixom, MI 48393
United States of America

T (248) 305 9707
E info@zimmermann-inc.com
W www.zimmermann-inc.com